

# Pulse Nutsetters

## Pulse Plus Series Nutrunner

Model Number	Soft Joint Torque Range			Soft Joint Torque Range			Speed rpm	Weight lbs	Length in.	Side to Center in.	Drive Size in.
	ft-lb	Nm	Kgf-cm	ft-lb	Nm	Kgf-cm					
PG247A-A5	16-24	20-32	202-330	17-25	23-34	239-349	8,000	2.10	5.70	1.86	1/4" Hex
PG307A-A5	19-30	25-41	257-413	20-30	27-41	275-413	6,000	2.20	6.50	1.86	1/4" Hex
PG347A-B1	16-27	22-36	220-370	19-28	26-3	270-390	8,000	2.10	5.70	1.86	3/8"
PG397A-B1	21-33	28-45	290-460	22-33	30-45	310-460	6,600	2.20	6.50	1.86	3/8"
PG537A-B1	35-52	47-70	480-710	33-50	45-68	460-690	7,000	3.10	7.00	1.96	3/8"
PG857A-D1	50-65	68-88	690-900	50-71	68-96	690-980	6,000	4.00	7.20	2.31	1/2"

Note:

Torque ranges are provided as a guide only.

Actual torque output will depend on joint type, air pressure, and type of accessories used.

## ARO Cordless Pulse Models

### Torque Range

- 6 to 14 ft.-lb.

### Accessories

- BP10P3-951-UL 1-hour Charger
- BP10P3-952-UL 90-minute Charger
- PBG147A-K2-UL 3/8" Square Drive Kit
- PBG147A-QK2-UL 1/4" Hex Quick Change Kit

### Kit Includes:

PGB147, extra battery pack (BP10P3-950), 1-hour Charger (BP10P3-951-UL) and Boot (BP10P-32).



PBG147A-A5

## Pulse Plus Series Nutrunner

Model Number	Soft Joint Torque Range			Soft Joint Torque Range			Speed rpm	Weight lbs	Length in.	Side to Center in.	Drive Size in.
	ft-lb	Nm	Kgf-cm	ft-lb	Nm	Kgf-cm					
PBG147A-A5	6-11	8-14	83-147	7-13	10-17	101-174	2,200	3.8 <sup>1</sup>	8.1	1.0	1/4" Hex
PBG147A-B1	7-12	9-16	90-160	8-14	11-19	110-190	2,200	3.8 <sup>1</sup>	8.1	1.0	3/8"

(1) Weight includes battery

Note:

Torque ranges are provided as a guide only.

Actual torque output will depend on joint type, air pressure, and type of accessories used.