

# Drills and Push-Pull Tapper

## Drills and Tappers

**Torque Output: 2.5 to 23.0 ft-lbs (3.4 to 31.2 Nm)**

### Standard Equipment

- Chuck

### Pistol Grip Drills

575 to 5,300 rpm / .7 hp (.5 kW)

950 to 3,800 rpm / .5 hp (.4 kW)

Capacity: 1/4" (6 mm) and 3/8" (9.5 mm)

- Model DG055A(-) and 8426(-) drills are excellent general purpose tools.



DG055A-21-B



8426-5

### Pistol Drills

Model No.	Speed rpm	Standard Chuck Cap.		Stall Torque		Spindle Thread Male	Spindle Offset		Tool Length		Tool Weight		@ Free Speed		Standard Chuck Part No.	
		in.	mm	ft-lbs	Nm		in.	mm	in.	mm	lbs	kg	Air Cons. cfm	Sound Level L/s dB(A)		
<b>Pistol</b>																
DG055A-38-F	3,800	5/16	8	2.5	3.4	3/8"-24	0.9	23	7.0	177	2.4	1.1	19	9.0	83	-
DG055A-21-B	2,100	3/8	10	4.5	6.1	3/8"-24	0.9	23	7.3	184	2.5	1.1	19	9.0	83	-
DG055A-10-L	950	1/2	13	10.0	13.6	3/8"-24	0.9	23	8.3	212	3.1	1.4	19	9.0	83	-
8426-2	5,300	3/8	9	3.7	5.0	3/8"-24	1.1	27	7.3	85	3.3	1.5	33	15.6	86	47341
8426-3	3,250	3/8	9	6.0	8.1	3/8"-24	1.1	27	7.3	185	3.3	1.5	33	15.6	86	47341
8426-4	2,600	3/8	9	7.4	10.0	3/8"-24	1.1	27	7.3	185	3.3	1.5	33	15.6	86	47341
8426-5	1,550	3/8	9	11.5	15.6	3/8"-24	1.1	27	9.0	229	3.8	1.7	33	15.6	86	30896
8426-6	950	3/8	9	19.5	26.4	3/8"-24	1.1	27	9.0	229	3.8	1.7	33	15.6	86	30896
8426-7	575	3/8	9	23.0	31.2	3/8"-24	1.1	27	9.0	229	3.8	1.7	33	15.6	86	30896
8525-C	2500	1/4	6	3.6	4.9	3/8"-24	0.9	22	6.0	153	2.7	1.2	26	12.3	84	41084
8526-C	4500	1/4	6	3.6	4.9	3/8"-24	0.9	22	6.0	153	2.7	1.2	26	12.3	84	41084

Air Inlet – 1/4" NPTF Recommended Air Pressure – 90 PSI (6.2 bar) Recommended Hose Size – 5/16" (8 mm) I.D.



8506-ADB



8506-ATA

### Quick Reverse Tappers (QRT)

Model No.	Speed rpm	Standard Chuck Capacity	Stall Torque		Spindle Thread Male	Spindle Offset		Tool Length		Tool Weight		@ Free Speed		Standard Chuck Part No.	
			in.-lbs	Nm		in.	mm	in.	mm	lbs	kg	Air Cons. cfm	Sound Level L/s dB(A)		
<b>Pistol</b>															
8506-ATA	600	NO. 0 - 1/4"	110	12.5	3/8"-24	0.9	23	8.2	208	2.7	1.2	24	11.3	82	31427
8506-ATB	600	NO. 10 - 5/16"	110	12.5	3/8"-24	0.9	23	8.2	208	2.7	1.2	24	11.3	82	31432
8506-ATC	600	5/16" - 5/8"	110	12.5	3/8"-24	0.9	23	8.2	208	2.7	1.2	24	11.3	82	32060
8509-ATA	900	NO. 0 - 1/4"	80	9.1	3/8"-24	0.9	23	8.2	208	2.7	1.2	26	12.2	82	31427
8509-ATB	900	NO. 10 - 5/16"	80	9.1	3/8"-24	0.9	23	8.2	208	2.7	1.2	26	12.2	82	31432
8509-ATC	900	5/16" - 5/8"	80	9.1	3/8"-24	0.9	23	8.2	208	2.7	1.2	26	12.2	82	32060
8506-ADB	600	3/8"	110	12.5	3/8"-24	0.9	23	8.0	203	2.9	1.3	24	11.3	82	47341
8506-ADK	600	1/2"	110	12.5	3/8"-24	0.9	23	8.0	203	2.9	1.3	24	11.3	82	34518
8509-ADB	900	3/8"	80	9.1	3/8"-24	0.9	23	8.0	203	2.9	1.3	26	12.2	82	47341
8509-ADK	900	1/2"	80	9.1	3/8"-24	0.9	23	8.0	203	2.9	1.3	26	12.2	82	34518

Air Inlet – 1/4" NPTF Recommended Air Pressure – 90 PSI (6.2 bar) Recommended Hose Size – 5/16" (8 mm) I.D.