

# 1/2" and 3/4" Drive Impact Wrenches

## Torque Output: 500 ft-lb (678 Nm)

### Industrial 1/2" Impact Wrenches

Model WG047A-D1 is a powerful industrial-grade tool for the most demanding fastening applications.

#### Features

- Built-in pressure-feed lubrication system
- Built-in power regulator
- Rugged steel hammer case (Model WG047A-D1)
- Integral muffler

#### Optional Equipment

Model WG047A-D1:

- 48951-161 Anvil Assembly with 7/16" Hex Quick-Change Chuck
- 48951-173 Anvil Assembly with 1/2" Square Ring Retainer

#### Accessories at Extra Cost

- 48951-94 Horizontal Hanger for Model WG047A-D1
- 48965 Service Kit for Model WG047A-D1



WG047A-D1

### 1/2" Impact Wrenches

Model Number	Drive Type	Free Speed rpm	Impacts per Minute	Max. Torque		Rec. Torque Range		Standard Bolt Cap.		Spindle Offset		Length		Weight	
				ft-lb	Nm	ft-lb	Nm	in.	mm	in.	mm	in.	mm	lbs	kg
<b>Industrial</b>															
WG047A-D1	1/2" Square	7,000	1,300	500	678	40-350	54-474	5/8	15.9	1.375	35	6.5	165	6.0	2.7

Air Inlet – 1/4" NPTF (Female) Recommended Air Pressure – 90 PSI (6.2 bar) Recommended Hose Size – 5/16" (8 mm) I.D.

# 3/4" Drive Impact Wrenches

## Torque Output: 1000 ft-lb (1360 Nm)

### Industrial 3/4" Impact Wrenches

#### Features

- Built-in pressure-feed lubrication system
- Smooth, efficient impact mechanism
- Steel hammer case
- Integral muffler

#### Accessories at Extra Cost

- 49852 Service Kit



WG068A-F4

### 1/2" Impact Wrenches

Model Number	Drive Type	Free Speed rpm	Impacts per Minute	Max. Torque		Rec. Torque Range		Standard Bolt Cap.		Spindle Offset		Length		Weight	
				ft-lb	Nm	ft-lb	Nm	in.	mm	in.	mm	in.	mm	lbs	kg
<b>Industrial</b>															
WG068A-F4	3/4" Square	5,500	1,000	1,000	1,360	200-600	271-813	3/4	19	2.28	48	7.625	194	11.625	5.39

Air Inlet – 3/8" NPTF (Female) Recommended Air Pressure – 90 PSI (6.2 bar) Recommended Hose Size – 1/2" (13 mm) I.D.