

3/8" Drive

Impact Wrenches

Torque Output: 125 ft-lb (169 Nm)

ARO is proud to offer a line of premium-quality, high-performance air impact wrenches. Durable, powerful, and easy-to-handle, they're ideal for use in a wide range of assembly, maintenance, and service operations.

Features include:

- The built-in Power Regulator lets you switch from lower power in one direction to full power in the opposite direction for extra performance when you need it most.
- A unique Pressure-Feed Lubrication System automatically distributes injected grease to the hammer mechanism to add longer, trouble-free service life.
- A rugged hammer design with fewer moving parts simplifies maintenance, reducing tool downtime and repair costs.
- Rotary hammering action delivers balanced blows for greater consistency and handling comfort.
- Reversible operation provides maximum utility.
- Models available in the most popular driver sizes with torque output of up to 1000 lb.ft. (1360 Nm).



WL037A-B1

Industrial and Economy 3/8" Impact Wrenches

Features

- Built-in pressure-feed lubrication system
- Built-in power regulator
- Smooth, efficient impact mechanism
- Rugged steel hammer case
- Integral muffler

Accessories at Extra Cost

- 48951-37 Vertical Hanger
- 48951-38 Horizontal Hanger
- Tune-up Kit for Model WG037A-()
- Tune-up Kit for Model WL037A-()
- 212-K23 Muffler Kit



WG037A-B1

3/8" Impact Wrenches

Model Number	Drive Type	Free Speed rpm	Impacts per Minute	Max. Torque		Rec. Torque Range		Standard Bolt Cap.		Spindle Offset		Length		Weight	
				ft-lb	Nm	ft-lb	Nm	in.	mm	in.	mm	in.	mm	lbs	kg
Straight															
WL037A-B1	3/8" Square	7,000	1,500	125	169	20-100	27-136	7/16	11	1.375	35	5.875	149	2.5	1.1
WL037A-A5	1/4" Hex Quick-Change	7,000	1,500	125	169	20-100	27-136	7/16	11	1.375	35	5.875	149	2.5	1.1
WL037A-C5	7/16" Hex Quick-Change	7,000	1,500	125	169	20-100	27-136	7/16	11	1.375	35	5.875	149	2.5	1.1
Pistol Grip															
WG037A-B1	3/8" Square	10,000	1,500	125	169	20-100	27-136	7/16	11	1.375	35	5.5	140	2.75	1.2
WG037A-A5	1/4" Hex Quick-Change	10,000	1,500	125	169	20-100	27-136	7/16	11	1.375	35	5.5	140	2.75	1.2
WG037A-C5	7/16" Hex Quick-Change	10,000	1,500	125	169	20-100	27-136	7/16	11	1.375	35	5.5	140	2.75	1.2

Air Inlet – 1/4" NPTF (Female) Recommended Air Pressure – 90 PSI (6.2 bar) Recommended Hose Size – 5/16" (8 mm) I.D.