

# Viscount II 1000, 2000 & 2600 Hydraulic Pumps

## Accessories

### GUNS AND TIPS

- 238591 Silver Plus Gun**  
Maximum working pressure: 5000 psi (34.5 MPa, 345 bar). With HD RAC tip and guard.
- 237162 HD RAC Tip Retainer**  
Maximum working pressure: 7400 psi (51 MPa, 510 bar). Fits guns with 7/8 in. (22.2 mm) thread, included as part of 236995 Model 510 Gun.
- 222674 HD RAC Tip Retainer With DripLess Guard**  
Inlet: 7/8 in. (22.2 mm) thread.
- GHDxxx HD RAC Tips**

### FLUID HOSES

#### Whip Hose

- Maximum working pressure: 3000 psi (20.7 MPa, 207 bar). ID 3/16 in. (5 mm). 1/4 npt(mbe).
- 214700** 2 ft. (0.6 m)  
**214701** 3 ft. (0.9 m)

#### Fluid Hose

- Maximum working pressure: 3000 psi (20.7 MPa, 207 bar). ID 3/8 in. (9.52 mm). 3/8 npt(mbe).
- 214703** 25 ft. (7.62 m)  
**214705** 50 ft. (15.24 m)  
**214920** 100 ft. (30.4 m)
- Maximum working pressure: 3000 psi (20.7 MPa, 207 bar). ID 1/4 in. (6.3 mm). 1/4 npsm(fbe).
- 223540** 25 ft. (7.62 m)  
**223541** 50 ft. (15.24 m)

### HYDRAULIC HOSES

#### Hydraulic Supply Line Hose

- Maximum working pressure: 2000 psi (14.0 MPa, 140 bar). ID 1/2 in. Coupled: 1/2 npt(m) x 3/4-16 SAE 37° flare(f), 90° swivel elbow, grounded.
- 180090** 3 ft. (0.9 m)  
**180093** 6 ft. (1.8 m)

#### Hydraulic Return Line Hose

- Maximum working pressure: 1500 psi (10.5 MPa, 105 bar). ID 5/8 in. Coupled: 3/4 npt(m) x 7/8-14 SAE 37° flare(f), 90° swivel elbow, grounded.
- 180091** 3 ft. (0.9 m)  
**180092** 6 ft. (1.8 m)

### CONTROLS AND VALVES

- 102644 Shut-Off Valve**  
For hydraulic supply or return line. 3/4 npt(f).
- 102646 Shut-Off Valve**  
For hydraulic supply or return line. 1 npt(f).
- Fluid Drain Valve (Carbon Steel)**  
Maximum working pressure: 5000 psi (34.5 MPa, 345 bar). Open to relieve fluid pressure in hose and gun/valve.
- 210657** 1/4 npt(mbe)  
**210658** 3/8 npt(mbe)  
**210659** 1/4 npt x 3/8 npt(mbe)

### ADAPTERS AND FITTINGS

#### Hose Swivel

- 214925** Maximum working pressure: 5000 psi (34.5 MPa, 345 bar). 3/8 npt(f) x 1/4 npsm(f).
- 236987** Maximum working pressure: 7400 psi (51 MPa, 510 bar). 1/4 npsm(m) x 1/4 npsm(f).
- 189018** Maximum working pressure: 5800 psi (39.9 MPa, 399 bar). 1/4 npsm(m) x 1/4 npsm(f).

#### 156173 Union Swivel

- Maximum working pressure: 7400 psi (51 MPa, 510 bar). Use to connect 3/8 in. (9.5 mm) hoses together. 3/8 npt(f) x 3/8 npsm(f).

#### 150287 Hose Coupler

- Maximum working pressure: 8000 psi (55 MPa, 550 bar). Use to connect 3/8 in. (9.5 mm) hose to whip hose. 3/8 npt(f) x 1/4 npt(m).

#### Gun Swivels (25 Pack)

- Maximum working pressure: 3600 psi (25 MPa, 250 bar). 1/4 npsm(f) x 1/4 npt(m).

- 239663** Leather  
**223341** Teflon

- Maximum working pressure: 5000 psi (34.5 MPa, 345 bar).

- 214925** Leather 1/4 npsm(f) 3/8 npt(f)  
**214926** Leather 1/2 npsm(f) 3/8 npt(f)

- Maximum working pressure: 5800 psi (48 MPa, 406 bar).

- 239394** Swivel with Built-in Filter

# Viscount II 1000, 2000 & 2600

## Hydraulic Pumps

### Accessories (continued)

#### Nipples

Use to connect hoses together.

- 156971** Maximum working pressure: 7500 psi (51.7 MPa, 517 bar).  
1/4 npt x 1/4 npt(mbe).
- 165198** Maximum working pressure: 10000 psi (69 MPa, 690 bar).  
1/4 npt x 3/8 npt(mbe).
- 162449** Maximum working pressure: 7400 psi (51 MPa, 510 bar).  
1/4 npt x 1/2 npt(mbe).
- 159239** Maximum working pressure: 7400 psi (51 MPa, 510 bar).  
3/8 npt x 1/2 npt(mbe).
- 158491** Maximum working pressure: 7400 psi (51 MPa, 510 bar).  
1/2 npt x 1/2 npt(mbe).

**184470 Fluid Outlet Reducer Fitting (CS)**  
Allows connection of 3/4 npt(f) hose 3/4 npt(m) x M42 x 2.0.

**237569 Grounding Wire**  
Length: 25 ft. (7.6 mm), 12 gauge (1.5 mm<sup>2</sup>).

### SUCTION KITS AND ACCESSORIES

#### Hydraulic Agitator and Drum Cover

**214906** Drum size: 55-gal. (200 L)

**184545 Suction Tube Extension**  
Screws into fluid intake to make a drum length pump.

**222916 Suction Kit, Carbon Steel**  
Connect to pump fluid inlet to draw fluid from 55-gal. (200 L) drum. Includes ID 1-1/2 in. 222914 polyethylene hose, 8 ft. (2.4 m) length and 2 npt(m) outlet fitting.

**236054 Siphon Kit, Carbon Steel**  
Use to siphon material out of 55-gal. (200 L) drum. Includes ID 3/8 in. 109105 nylon suction hose, 6 ft. (1.8 m) long, 1-1/2 npt(m) outlet fitting.

**208920 Siphon Kit, Aluminum**  
Use to siphon fluid from a 5-gal. (18.9 L) pail. Includes ID 1 in. 170706 nylon suction hose, 4 ft. (1.2 m) long, 3/4 npt(f) swivel outlet fitting.

**207484 Siphon Kit, Aluminum**  
Use to siphon fluid from a 5-gal. (18.9 L) pail. Includes ID 3/4 in. 214960 nylon suction hose, 3.5 ft. (1.1 m) long, 3/4 npt(f) swivel outlet fitting.

**208259 Siphon Kit, Carbon Steel**  
Use to siphon fluid from a 55-gal. (200 L) drum. Includes 214961 ID 3/4 in. nylon suction hose, 6 ft. (1.8 m) long, 3/4 npt(f) swivel outlet fitting and bung adapter.

### FILTERS

#### Replacement Screen Filter Elements

3 Pack	25 Pack	
<b>238435</b>	<b>238436</b>	30 mesh (595 micron)
<b>238437</b>	<b>238438</b>	60 mesh (250 micron)
<b>238439</b>	<b>238440</b>	100 mesh (149 micron)
<b>238441</b>	<b>238442</b>	200 mesh (75 micron)

#### Red Alert Filters

Built-in bypass with pop-up indicator.

<b>207994</b>	with 30 mesh (595 micron) element
<b>207995</b>	with 60 mesh (250 micron) element
<b>207996</b>	with 100 mesh (149 micron) element
<b>207997</b>	with 150 mesh element
<b>207998</b>	with 200 mesh (75 micron) element

#### 238620 Fluid Filter (Carbon Steel)

Maximum working pressure: 5000 psi (34.5 MPa, 345 bar). SST screen: 60 mesh (250 micron).  
Outlets: 3/4 npt(f). Inlet: 3/8 npt(f) and 1/2 npt(f).  
Includes 210658 drain valve.

### LIQUIDS AND LUBRICATION

#### Graco Throat Seal Liquid

<b>206995</b>	1 qt. (0.9 L)
<b>206996</b>	1 gal. (3.8 L)

#### Graco-Approved Hydraulic Fluid

<b>169236</b>	5 gal. (20 L)
<b>207428</b>	1 gal. (3.8 L)

#### 222955 Anti-Seize Lubricant

Prevents parts from seizing, making disassembly easier.  
Can size: 16 oz. (454 g).

### MOUNTING OPTIONS

#### 222976 Connection Kit, Viscount II 2000 and 2600

Kit to install lower displacement pump under existing Viscount II motor. Includes carbon steel tie rods and other connecting hardware.

#### 244849 Xtreme Connection Kit

Kit to install Xtreme pump lower under existing Viscount II motors. Includes tie rods, rod adapter and quick disconnect coupler.

#### 244530 Heavy-Duty 2-Wheel Cart

#### 244527 Lightweight 2-Wheel Cart

#### 222780 Floor Stand

Use to mount Viscount II 2000 and 2600 pumps to floor. Includes 222274 floor stand, ball valve and 109495 Viton gasket.

#### 206221 Wall Mounting Bracket

#### 237782 Adapter, Ram

Use to mount Viscount II 2000 and 2600 pumps to a ram. Includes 2 npt(m) x flange and lug kit.

# Viscount II 1000, 2000 & 2600

## Hydraulic Pumps

### Accessories (continued)

#### TOOLS

**109507 Socket Service Tool, Viscount II 2600**

Use to connect or disconnect displacement rod from piston assembly. Tool fits over the top of the displacement rod, making it easier to apply a 24 in. adjustable wrench or 3/4 in. drive socket for servicing displacement rod.

**109508 Socket Service Tool, Viscount II 2000**

Use to connect or disconnect displacement rod from piston assembly. Tool fits over the top of the displacement rod, making it easier to apply a 24 in. adjustable wrench or 3/4 in. drive socket for servicing displacement rod.

**184278 Packing Nut Wrench, Viscount II 2000 and 2600**

For adjusting throat packing compression in pump.