

# Pump Performance

- Air Inlet Pressure Range . . . . . 30 - 90 PSI (2 - 6.1 bar)
- Fluid Pressure Range . . . . . 3450 - 1,350 PSI (91.8 bar)
- Max. Rec'd Cycles Per Minute . 60
- Displacement Per Cycle . . . . . 59.9 in<sup>3</sup> (981.5 cm<sup>3</sup>)
- Cycles Per Gallon (Liter) . . . . . 3.8 (1.01)
- Flow @ 60 Cycles / Minute . . . . 15 GPM (56.7 lpm)
- Noise Level @ 60 Psi . . . . . 82 db(A) w/muffler

# Pump Specifications

- Lower Pump Material . . . . . 304 Stainless Steel
- Plunger Material . . . . . 15-5 Stainless Steel (Chrome Plated)
- Cylinder Material . . . . . 15-5 Stainless Steel (Chrome Plated)
- Air Motor . . . . . 66651-B
- Motor Repair Kit . . . . . 637110
- Motor Diameter . . . . . 10"
- Stroke . . . . . 6"
- Air Inlet . . . . . 3/4" NPT(F)
- Lower Pump End Series . . . . . 66942-XXF
- Lower Pump Repair Kit . . . . . 637211-XXX
- Material Inlet . . . . . 2" NPT(M)
- Material Outlet . . . . . 1-1/4" NPT(F)
- Weight . . . . . 125 lbs. (56.8 kgs.)



613123-XXF-C

# Ordering

6 1 3 1 2 3 -X X F -C

**Packings**

- C6 : UHMW-PE
- K3 : CG-Filled Teflon with, Buna N Energizer
- L6 : Mineral-Filled Teflon
- P6 : UHMW-PE/Teflon (Upper), UHMW-PE (Lower)
- R6 : Teflon/UHMW-PE (Upper), Teflon (Lower)

# Accessories

- Air F/R/L: 28353
- Wall Mount: 66542
- Airline Oil: 62274
- Muffler: 66718
- Wet Sol: 66333-B

