

# EZ Paint Mixing Room

- EZ to Install
- EZ to Operate
- EZ to Maintain
- EZ to Quick Ship

Col-Met's EZ product line was developed to provide fast availability and simple installation. Easy to maintain and operate, our Paint Mix Rooms provide a controlled area for safely mixing paint.

Air flows in through the filtered air intake, which is located in the ceiling toward one end of the room. It moves downward through the work area and into the exhaust chamber located in the lower opposite end of the room. Filtered exhaust is drawn through the exhaust plenum and is discharged upward into the atmosphere through the exhaust stack.



## Features

- >> **Heavy Duty Construction** Wall panels constructed from 18-gauge, prime quality galvanized steel. All panels and support members are precision punched for easy nut and bolt assembly.
- >> **Superior Lighting** Lighted booths get bright, full booth illumination from four-tube, 48" long, 32-watt, fluorescent light fixtures. Col-Met light fixtures are ETL listed (Class 1 Division 2, Groups A, B, C, D and Class 2 Division 2, Groups F and G)
- >> **Fan & Motor** Quality brand name tubeaxial fans and motors
- >> **Exceptional Doors** Personnel access doors are pre-hung in a heavy gauge galvanized steel frame for easy installation

## Options

- >> Goff™ Curtain Walls optional for closing of painting area (installed height is required)
- >> Control panel and other electrical components can be purchased separately
- >> Easy addition of heated air makeup unit



UL & ETL listed control panel



Industry-leading light levels



Windowed personnel access doors



5/16" bolts with serrated lock nut

# EZ Paint Mixing Room



Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Qty. Lights	Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length				Dia.	HP	Int.	Exh.
PMR-08-08-08	8'-0"	8'-0"	8'-0"	8'-4"	8'-2"	10'-6"	1 with window	1	1,450	12"	3/4 HP	4	2
PMR-08-08-10	8'-0"	8'-0"	10'-0"	8'-4"	8'-2"	12'-6"	1 with window	2	1,450	12"	3/4 HP	4	2
PMR-08-08-12	8'-0"	8'-0"	12'-0"	8'-4"	8'-2"	14'-6"	1 with window	2	1,450	12"	3/4 HP	4	2
PMR-08-08-15	8'-0"	8'-0"	15'-0"	8'-4"	8'-2"	17'-6"	1 with window	3	1,450	12"	3/4 HP	4	2
PMR-10-08-15	8'-0"	8'-0"	15'-0"	8'-4"	8'-2"	17'-6"	1 with window	3	1,450	12"	3/4 HP	4	2
PMR-08-08-08	8'-0"	8'-0"	8'-0"	8'-4"	8'-2"	10'-6"	1 with window	1	1,450	12"	3/4 HP	4	2
<b>Ref. Key</b>	<b>A</b>	<b>B</b>	<b>C</b>		<b>D</b>								

