

# Hydra-Clean<sup>®</sup> Pressure Washers

High Sanitation Cleaning Packages



## Spray down portability for sanitary applications

- Efficient cleaning with water, detergent or chemical solutions
- Supports multiple guns
- Designed to use with cold or hot water up to 200°F (93°C)
- Use with open-head universal drums
- Fits most pressure, flow and material requirements

PROVEN QUALITY. LEADING TECHNOLOGY.

# Ordering Information

Package Order Number	247549 or 247550	247551 or 247552	247553 or 247554	258664 or 258665	206515
Package Instruction Manual	312585	312585	312585	312585	306817
Air Motor Part Number	N34DN0	N65DN0	N65DN0	N65DN0	207352
Air Motor Manual	311238	311238	311238	311238	306982
Pump Lower Part number	247599	241648	687055	24B923	224344
Pump Manual	312745	311825	311825	311827	306817
Wetted Parts	SST/PTFE/ CF-PTFE	SST/CF-PTFE/ UHMWPE	SST/CF-PTFE/ UHMWPE	SST/CF-PTFE/ UHMWPE	SST/CR/ UHMWPE
Pump Std. Repair Kit	247881	222880	See Maul	24C162	224402
Optional PTFE Repair Kit	N/A	222876	222846	237179	224889
Std. Discharge hose (3/8 x 50 ft) 4500 psi with M & F QD's	247878	247878	247878	247878	205753
Std. Gun/Wand Assy	247879	247879	247879	247879	237485/207299
Std. 60 Mesh Inlet Strainer	15T284	15T284	15T284	15T284	206300



Hydra-Clean Wall-Mount



Hydra-Clean Cart-Mount



Hydra-Clean Drum-Mount

## Spray Tips

Part Number	Orifice Size	Fan Angle	247549 or 247550	247551 or 247552	247553 or 247554	248664 or 248665	206515
805538	0.030 in (0.8 mm)	40°	1165 psi (80 bar) 0.6 gpm (2.3 lpm)	2120 psi (146 bar) 0.8 gpm (3.0 lpm)	2829 psi (195 bar) 1.0 gpm (3.8 lpm)	3995 psi (275 bar) 1.2 gpm (4.5 lpm)	N/A
805549	0.045 in (1.1 mm)	25°	1137 psi (78 bar) 1.7 gpm (6.4 lpm)	2020 psi (139 bar) 1.8 gpm (6.8 lpm)	2553 psi (176 bar) 2.0 gpm (7.6 lpm)	3515 psi (242 bar) 3.3 gpm (12.5 lpm)	N/A
805566	0.065 in (1.7 mm)	40°	1071 psi (74 bar) 3.6 gpm (13.6 lpm)	1803 psi (124 bar) 3.7 gpm (14.0 lpm)	2141 psi (148 bar) 4.0 gpm (15.1 lpm)	2924 psi (201 bar) 4.1 gpm (15.2 lpm)	N/A
805575	0.080 in (2.0 mm)	0°	1018 psi (70 bar) 4.0 gpm (15.1 lpm)	1634 psi (113 bar) 4.8 gpm (18.1 lpm)	1811 psi (125 bar) 4.9 gpm (18.5 lpm)	2499 psi (172 bar) 5.1 gpm (19.3 lpm)	N/A
103921	0.065 in (1.6 mm)	40°	N/A	N/A	N/A	N/A	750 psi (52 bar) 2.6 gpm (9.8 lpm)

Pressure and flow rates are tested with air pressure of 100 psi (7 bar).

Other orifice sizes and fan widths available from Graco. Contact a sales representative for more information.

## Accessories

### GUNS AND WANDS

- 15T282** Optional replacement SST spray gun
- 15T279** 32 in (81 cm) SST wand
- 15T280** 10 in (25 cm) SST wand
- 247880** Gun SST quick disconnect connections

### OTHER

- 191635** 10 mesh inlet strainer with 1 in npt(f) connection
- 15T272** Quick Coupling  
For adding a second hose with gun to the outlet of the pump

## Technical Specifications

Part Number	Pump Package	Max. Working Pressure	Max. Air Input Pressure	Fluid Flow at 60 cpm	Volume per Cycle	Air Inlet Size	Fluid Inlet Size	Fluid Outlet Size
247549	12:1 Cart Mount	1250 psi (86 bar, 8.6 MPa)	100 psi (7 bar, 0.7 MPa)	8.7 gpm (33.0 lpm)	18.6 oz (550 cc)	3/4" npt(f)	1 in	3/8 in
247550	12:1 Wall Mount	1250 psi (86 bar, 8.6 MPa)	100 psi (7 bar, 0.7 MPa)	8.7 gpm (33.0 lpm)	18.6 oz (550 cc)	3/4" npt(f)	1 in	3/8 in
247551	23:1 Cart Mount	2275 psi (157 bar, 15.7 MPa)	100 psi (7 bar, 0.7 MPa)	9.2 gpm (34.7 lpm)	19.6 oz (580 cc)	3/4" npt(f)	1 in	3/8 in
247552	23:1 Wall Mount	2275 psi (157 bar, 15.7 MPa)	100 psi (7 bar, 0.7 MPa)	9.2 gpm (34.7 lpm)	19.6 oz (580 cc)	3/4" npt(f)	1 in	3/8 in
247553	30:1 Cart Mount	3065 psi (211 bar, 21.1 MPa)	100 psi (7 bar, 0.7 MPa)	6.8 gpm (25.9 lpm)	14.5 oz (430 cc)	3/4" npt(f)	1 in	3/8 in
247554	30:1 Wall Mount	3065 psi (211 bar, 21.1 MPa)	100 psi (7 bar, 0.7 MPa)	6.8 gpm (25.9 lpm)	14.5 oz (430 cc)	3/4" npt(f)	1 in	3/8 in
258664	45:1 Cart Mount	4500 psi (310 bar, 31.0 MPa)	100 psi (7 bar, 0.7 MPa)	4.6 gpm (17.4 lpm)	9.8 oz (290 cc)	3/4" npt(f)	1 in	3/8 in
258665	45:1 Wall Mount	4500 psi (310 bar, 31.0 MPa)	100 psi (7 bar, 0.7 MPa)	4.6 gpm (17.4 lpm)	9.8 oz (290 cc)	3/4" npt(f)	1 in	3/8 in
206515	10:1 Drum Mount	1800 psi (125 bar, 12.5 MPa)	180 psi (12.5 bar, 1.2 MPa)	3.0 gpm (11.4 lpm)	6.4 oz (189 cc)	1/2" npt(f)	1/2 in	3/4 in

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

**877.84GRACO** (1-877-844-7226) or visit us at [www.graco.com/hydraclean](http://www.graco.com/hydraclean)

©2013 Graco Inc. Form No. 338026 Rev. E 06/13 Printed in the U.S.A.

All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

