



**Chicago  
Pneumatic**



# **CP7763D/73D**

**3/4" & 1" Impact Wrenches**  
**Available in Short or 6" Extended Anvils**



- ✓ **Great Performance**
- ✓ **Higher Durability**
- ✓ **Lightweight**



**Vehicle  
Service** Tools

**People. Passion. Performance.**

# CP7763D/73D

## 3/4" & 1" Impact Wrenches Available in Short or 6" Extended Anvils

### Great Performance & Durability

1300 ft.lbs - 1760 Nm of maximum torque in reverse

### HIGH DURABILITY & POWERFUL

- Twin hammer mechanism
- Steel motor

### RUGGED & ROBUST

- Aluminum housing
- Composite cover

### SAFE


Socket retainer ring

### COMFORT

- Ergonomic handle
- Side handle with soft touch grip
- Down exhaust

### EASY TO USE

- 4 position power regulator on both sides
- Ergonomic Forward / Reverse lever



### DIMENSIONS

MODEL	A		B		C	
	in.	mm	in.	mm	in.	mm
CP7763D	11.4	290	6.5	165	3.5	90
CP7763D-6	17.5	445	6.5	165	3.5	90
CP7773D	11.4	290	6.5	165	3.5	90
CP7773D-6	17.5	445	6.5	165	3.5	90

Model	Part number	Square Drive inch	Working Torque		Max Torque		Speed RPM	Weight		Air Consumption average		Air Consumption @ load		Sound Level dBA	Vibration m/s <sup>2</sup> (k)
			ft.-lbs.	Nm	ft.-lbs.	Nm		lbs	kg	cfm	l/s	cfm	l/s		
CP7763D	894 107 7631	3/4"	250 - 1070	340 - 1450	1300	1760	6600	14.3	6.5	10.5	4.4	41	19.2	98	12 - (3.3)
CP7763D-6	894 107 7637	3/4"	250 - 1070	340 - 1450	1300	1760	6600	16.1	7.3	10.5	4.4	41	19.2	98	12 - (3.3)
CP7773D	894 107 7731	1"	250 - 1070	340 - 1450	1300	1760	6600	14.5	6.6	10.5	4.4	41	19.2	98	12 - (3.3)
CP7773D-6	894 107 7737	1"	250 - 1070	340 - 1450	1300	1760	6600	16.3	7.4	10.5	4.4	41	19.2	98	12 - (3.3)

All models: Hose int. 1/2" (13 mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check tool documentation.

### DEEP SOCKET SETS

Model	Part #	Size	8 pieces set
SS618D	894 016 4473	3/4"	26, 27, 29, 30, 32, 35, 36, 38 mm
SS6008D	894 016 7073	3/4"	1, 1-1/16, 1-1/8, 1-1/4, 1-3/8, 1-7/8, 1-7/16, 1-1/2"
SS818D	894 016 4477	1"	27, 30, 32, 33, 35, 36, 38, 41 mm
SS808D	894 016 4479	1"	7/8, 15/16, 1, 1-1/16, 1-1/8, 1-3/8, 1-1/4, 1-1/2"

### NEW 2 STAGE COMPOSITE FRL

Part # NPT	Part # BSP	Size	Max. Flow Rate	
		in.	cfm	l/sec
894 017 1944	894 017 1927	1/4"	74	34
894 017 1946	894 017 1929	1/2"	96	44

### TUNE-UP KIT

Model	Tune-up Kit
CP7763D(-6) CP7773D(-6)	894 017 3716

Chicago Pneumatic also offers a large range of air tools, accessories, and workshop equipment to optimize your air tools durability and performance: Check [www.cp.com](http://www.cp.com) website for more information.



[www.cp.com](http://www.cp.com)